



Every facility is different. Ascension offers the ability to fit your lift to your specific needs.

Standard	●
Optional	○
Not Available	-
External to Lift, Optional	❖

Lift Options	Clarity	Virtuoso		Protégé	
	Permanent	Portable	Permanent	Portable	Permanent
Automatic Gate Operator(s), Upper and/or Lower	○	○	○	○	○
Communication - Two Way	○	○	○	○	○
Compression Feature	-	●	●	●	●
Drive System - Chain Hydraulic	●	-	-	-	-
Drive System - Direct Hydraulic	-	●	●	●	●
Electrical – Internal Battery Backup	●	❖	❖	❖	❖
Electrical Configured for 230VAC	○	○	○	○	○
Enclosure – Dome & Ventilation	○	-	-	-	-
Enclosure – Full Aluminum/Plexiglas Runway	●	-	-	-	-
Enclosure – Installed in Shaft/Runway By Others	○	-	-	-	○
Entry/Exit - Same Side	○	-	-	-	-
Entry/Exit - Straight Through	●	●	●	●	●
Key Switches – Universal	○	○	○	○	○
Lighting - 3-Mode Accent Lighting in Grab Bar	●	-	-	-	-
Lighting - Emergency	●	○	○	○	○
Outdoor Use Package	○	○	○	○	○
Powder Coating - Black Texture	○	●	●	●	●
Powder Coating - Custom Color	○	○	○	○	○
Powder Coating - Silver Metallic	●	○	○	○	○
Safety Pan - Under Platform	-	○	○	●	●
Safety Skirt	-	●	●	-	-

Physical Dimensions			
Platform Size	36" x 56"	36" x 54"	
Lift Size	48" x 68"	48" x 63"	48" x 58"
Required Space	48" x 68"	52" x 64"	52" x 61"
Vertical Speed (ft per min)	20	7	5
Vertical Travel Range	34" - 168"	12" - 60"	4" - 42"

**Standard in all lifts:**

Unobstructed View on Three Sides + Upper Landing Gate Window, No Machine Room Needed, Ultra-Slim Platform Floor, Vibration-Isolated Power Unit Supports, Grab Bar, Self-Closing Platform Gates, Electro-Mechanical Door and Gate Interlocks, Lighted Emergency Stop Button with Alarm, Slip-Resistant Platform Floor, Power Requirement: 120V, 13A Max.