

# ASCENSION

WHEELCHAIR LIFTS

## Lift Features



[ascension-lift.com](http://ascension-lift.com)  
Call: 520-881-3993



Standard	✓
Optional	☐
Not Available	-
Standard on Unenclosed Version	●
External to Lift, Optional	☒

Lift Options	Clarity	Virtuoso		Protégé	
	Permanent	Portable	Permanent	Portable	Permanent
Accordion-Style PVC Safety Skirt	-	✓	✓	-	-
Built-In Backup Power	✓	☒	☒	☒	☒
Compression Feature	-	✓	✓	✓	✓
Custom Color	☐	☐	☐	☐	☐
Drive System (Built into Sides)	-	✓	✓	✓	✓
Dual-Cylinder, Electro-Hydraulic Drive System	-	✓	✓	✓	✓
Dual-Cylinder, Four-Chain Hydraulic Drive System	✓	-	-	-	-
Emergency Lighting	✓	☐	☐	☐	☐
Full Enclosure with Transparent Panels	✓	-	-	-	-
Integral, 3-Mode Lighting System in Grab Bar	✓	-	-	-	-
Landing-Face-Mounted Machinery Cabinet	✓	-	-	-	-
Outdoor Dome	☐	-	-	-	-
Outdoor-Rated, Black-Textured Powder Coating	☐	✓	✓	✓	✓
Outdoor-Rated, Silver-Metallic Powder Coating	✓	☐	☐	☐	☐
Power Gate Operator, Upper and/or Lower	☐	☐	☐	☐	☐
Power Requirement: 230V, 10A	☐	☐	☐	☐	☐
Pre-Wiring for Two-Way Communication	☐	☐	☐	☐	☐
Straight Through Cab Access	☐	-	-	-	-
Suitable For Outdoor Use	☐	☐	☐	☐	☐
Three Field-Selectable Lighting Modes	✓	-	-	-	-
Two-Way Communication Built Into Control Panel	☐	-	-	-	-
Under-Platform Safety Pan	●	-	-	✓	✓
Universal Keys	☐	☐	☐	☐	☐
Physical Dimensions					
Footprint	48" x 68"	48" x 66"		48" x 61"	
Min Installation Footprint (w/clearance)	48" x 68	52" x 66		52" x 61"	
Platform Clear Space	36" x 56"	36" x 54"			
Vertical Speed (ft per min)	17	7		5	
Vertical Travel Range	34" - 168"	12" - 60"		4" - 42"	

### Standard in all lifts:

Unobstructed View on Three Sides + ULG Window, Ultra-Slim Platform Floor, Vibration-Isolated Power Unit Supports, Stainless Steel Grab Bar, Self-Closing Platform Gates, Electro-Mechanical Door and Gate Interlocks, Lighted Emergency Stop Button with Alarm, Slip-Resistant Platform Floor, Power Requirement: 110V, 10A